



## Product Specification Guide

Product Name: **SYDNEY HARBOUR'S ALCHEMY LIQUID GOLD**

---

### PRODUCT DESCRIPTION:

Use Sydney Harbour's Alchemy Liquid Gold to create large-scale drama on broad wall areas, or just add a subtle touch of luxury and sophistication to trim, picture frames and furniture. Sydney Harbour's Alchemy Liquid Gold is a water based decorative metallic gold for use on a variety of interior and exterior surfaces. Suitable for broad wall areas and small areas like trims, picture frames and furniture.

### LOCATION:

Interior or exterior. When left to weather on exterior surfaces Liquid Gold may, over time, become slightly duller and due to the small amount of copper present in the gold pigment, may also exhibit some green oxidation.

### ENVIRONMENTAL INFORMATION:

This product contains: 40.08 g/L VOC.

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes are designed for maximum performance with

minimum impact on the environment and user health.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, metal, masonry and previously painted surfaces.

### COLORS:

Available in Bronze Gold, Rose Gold and Antique Gold.

### LIMITATIONS:

Visible brushstrokes are a characteristic of metallic and pearlescent paints and it is for this reason that we do not recommend application with a paint roller. Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

## **PREPARATION:**

### **NEW/UNPAINTED SUBSTRATES:**

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mold. Dust down before proceeding. On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply two coats of same to entire area. Touch dry 2 hours. Allow 6 hours dry time between coats, and 6 hours dry time when painting is complete.

On bare metallic surfaces, apply a suitable metallic primer (anti-corrosive), then apply two coats of Sydney Harbour's Universal Primer. Touch dry 2 hours. Recoat 6 hours. Allow to dry 24 hours. On galvanized iron only Universal Primer is necessary.

### **PREVIOUSLY PAINTED SUBTRATES:**

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry 2 hours. Allow 6 hours dry time.

## **APPLICATION:**

Stir thoroughly prior to use. Apply two coats by brush or spray. When painting broad wall areas using a brush, best results are achieved by laying off or reworking paint as applied (usually in a vertical direction) to achieve a smoother effect. Spraying will achieve a finer smoother effect than brushing. Touch dry in 1 hour. Allow minimum 4

hours dry time between coats. Allow total 6 hours dry time.

## **COVERAGE RATES:**

Approximately 400 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates.

## **CLEAN UP:**

Water.

## **COMPLEMENTARY PRODUCTS:**

Sydney Harbour's Limeproof Undercoat Sealer (coverage 450 sq. ft. per gallon) is recommended where an undercoat/primer is required when preparing substrate for painting.

Sydney Harbour's Universal Primer (coverage 400 sq. ft. per gallon) is recommended on metallic surfaces after a suitable metal primer has been applied.

## **PACKAGING:**

Sydney Harbour's Alchemy Liquid Gold is available in Pint, Quart, and Gallon sizes.

## **STORAGE:**

Store in a cool dry area, protected from frost.

## **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact

occurs, rinse immediately with water. Check color before use.

#### **MANUFACTURER/DISTRIBUTOR DETAILS:**

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: [admin@shpcompany.com](mailto:admin@shpcompany.com)

Web: [www.SHPCompany.com](http://www.SHPCompany.com)