



## Product Specification Guide

Product Name: **SYDNEY HARBOUR'S CHALKBOARD PAINT**

---

### PRODUCT DESCRIPTION:

Sydney Harbour's Chalkboard Paint is perfect for making your own chalkboards in cafés, kitchens, workplaces and children's play areas. Available in traditional black and a fun range of bright bold colors. Dries to a smooth finish for easy cleaning. Has a superb creamy texture, excellent coverage.

### LOCATION:

Interior or exterior.

### ENVIRONMENTAL INFORMATION:

This product contains:  $\leq 29.74$  g/L VOC.

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

### SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

### COLORS:

Choose from our large range of colors, or ask our colorist for your own custom color.

### LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

### PREPARATION:

#### NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mold. Dust down before proceeding.

On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply two coats of same to entire area.

#### PREVIOUSLY PAINTED SUBSTRATES:

Provided the surface is clean and sound, Sydney Harbour's Chalkboard Paint can be applied directly over previously painted surfaces.

Previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply two coats to entire area. Touch dry two hours. Allow 6 hours dry time.

#### **APPLICATION:**

Stir thoroughly prior to use. Apply two coats by brush or a medium nap roller. Touch dry in 30 minutes. Allow minimum 2 hours dry time between coats. Allow 48 hours dry time before use as a chalkboard.

#### **CARE OF YOUR CHALKBOARD**

Chalk can be removed with ordinary blackboard dusters, however, for best results clean with a damp sponge or rag.

#### **COVERAGE RATES:**

Approximately 400 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates.

#### **WASH UP:**

Water.

#### **COMPLEMENTARY PRODUCTS:**

Sydney Harbour's Limeproof Undercoat Sealer (coverage 450 sq. ft. per gallon) is recommended where an undercoat/primer is required when preparing substrate for painting.

#### **PACKAGING:**

Sydney Harbour's Chalkboard Paint is available in Quart and Gallon sizes.

#### **STORAGE:**

Store in a cool dry area, protected from frost.

#### **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use.

#### **MANUFACTURER/DISTRIBUTOR DETAILS:**

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: [admin@shpcompany.com](mailto:admin@shpcompany.com)

Web: [www.SHPCcompany.com](http://www.SHPCcompany.com)