



## Product Specification

Product Name: **SYDNEY HARBOUR'S WOOD WASH**

---

### PRODUCT DESCRIPTION:

Sydney Harbour's Wood Wash is a translucent coating that subtly softens and ages the appearance of bare timber, highlighting the grain and replicating the look of limed timber. Wood Wash is supplied as a neutral white base that can be tinted to any color.

### LOCATION:

Interior.

### ENVIRONMENTAL INFORMATION:

This product contains:  $\leq 67.2\text{g/L VOC}$ .

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

### SUGGESTED APPLICATIONS:

Can be applied to most bare timber furniture, floorboards, lining boards or timber trim.

### COLORS:

Choose from our range of colors, or ask our colorist for your own custom color.

### LIMITATIONS:

Not suitable for use over some tannin rich timbers, such as Western Red Cedar. Not suitable for use on arsenic treated timber. Always test prior to use. Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

### PREPARATION:

Substrate should be sanded to expose clean bare timber free from paint, dirt, grease, oil and previous coatings. Dust down before proceeding.

### APPLICATION:

Stir thoroughly prior to use.

*First coat* – apply Sydney Harbour's Wood Wash by brush or lamb's wool applicator, following the grain of the timber. Within 3-4 minutes wipe off excess Wood Wash with muslin or lint-free cloth

to achieve desired pattern and depth of color.  
Touch dry 2-4 hours. Allow to dry for 24 hours.

*Second coat (for a more opaque effect - optional)*  
– Allow first coat to dry for 24 hours then apply a second coat as per first coat. Allow 24 hours dry time.

#### **COVERAGE RATES:**

Sydney Harbour's Wood Wash covers approximately 750 to 800 sq. ft. per gallon, depending upon porosity, surface texture, and wastage rates.

#### **CLEAN UP:**

Water.

#### **COMPLEMENTARY PRODUCTS:**

Sydney Harbour's Wood Wash can be sealed and protected with Sydney Harbour's Clearcote (coverage 600 sq. ft. per gallon). Allow Wood Wash to dry for 72 hours before applying Clearcote. Test before use as a slight color variation may occur or tannin bleed may become evident.

#### **PACKAGING:**

Sydney Harbour's Wood Wash is available in Pint, Quart, and Gallon sizes.

#### **STORAGE:**

Store in a cool dry area, protected from frost.

#### **PRECAUTIONS:**

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use.

#### **MANUFACTURER/DISTRIBUTOR DETAILS:**

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: [admin@shpcompany.com](mailto:admin@shpcompany.com)

Web: [www.SHPCompany.com](http://www.SHPCompany.com)