



Product Specification

Product Name: **SYDNEY HARBOUR'S AQUA ENAMEL**

PRODUCT DESCRIPTION:

Sydney Harbour's Aqua Enamel is a water based acrylic enamel that dries to a hardwearing finish that provides all the benefits of an oil based enamel with none of the drawbacks. Available in Gloss (super shine) or Satin finish. Self-leveling (to minimize brush marks), non-yellowing, tough wearing, long lasting with excellent gloss retention, easy to apply, low odor, low VOC, fast drying with easy re-coat. Excellent for exterior woodwork and trim areas as its high UV resistance ensures durability and longevity in a range of temperature and climatic conditions. Sydney Harbour's Aqua Enamel resists peeling and flaking and is fully washable.

LOCATION:

Interior and exterior. Ideal for doors, architraves, windows and trim.

ENVIRONMENTAL INFORMATION:

This product contains: <50 g/L VOC.

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes

are designed for maximum performance with minimum impact on user health and the environment.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, metal, wood, masonry and previously painted surfaces.

COLORS:

Choose from our large range of colors, or ask our colorist for your own custom color. Available in Gloss or Satin finish.

LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mold.

Dust down before proceeding. On bare surfaces such as new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Sydney Harbour's Universal Primer, then apply one coat of same to entire area. Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Aqua Enamel.

PREVIOUSLY PAINTED SUBTRATES:

When painting over a water based acrylic paint, provided the surface is clean, sound and sanded to remove gloss, Sydney Harbour's Aqua Enamel is self-priming and can be applied direct. All varnishes, polyurethanes or surfaces previously painted with oil based enamel paint should be thoroughly sanded to remove gloss and to create a "keyed" surface. Loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Sydney Harbour's Universal Primer, then apply one coat of same to entire area.

Touch dry 2 hours. Allow 6 hours dry time between coats and 24 hours dry time prior to the application of Aqua Enamel.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, short nap roller or spray. Touch dry in 1 hour. Allow minimum 3 hours dry time between coats. Allow 8 hours dry time.

COVERAGE RATES:

Approximately 400 to 500 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates.

CLEAN UP:

Water.

COMPLEMENTARY PRODUCTS:

Sydney Harbour's Universal Primer (coverage 400 sq. ft. per gallon) is also recommended. Gives a smoother overall result.

PACKAGING:

Sydney Harbour's Aqua Enamel is available in Quart and Gallon sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use.

MANUFACTURER/DISTRIBUTOR DETAILS:

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: admin@shpcompany.com

Web: www.sydneyharbourpaints.com