



Product Specification

Product Name: **SYDNEY HARBOUR'S EGGSHELL ACRYLIC**

PRODUCT DESCRIPTION:

Sydney Harbour's Eggshell Acrylic is a superior quality acrylic paint that gives walls and other surfaces a low reflective finish with an elegant, natural luster like the subtle sheen of real eggshell. This chic finish is fully washable and resistant to scratches and knocks. Fast drying, self-priming, and VOC free.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

This product contains: <1 g/L VOC.

- Southern California Air Quality Management District Rule 314 compliant
- LEED v4 & v4.1 eligible

Sydney Harbour uses only premium grade raw materials. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared plasterboard, plaster, wood, masonry and previously painted surfaces.

COLORS:

Choose from our large range of colors, or ask our colorist for your own custom color.

LIMITATIONS:

Do not apply in high humidity, below 50°F or above 86°F, or when temperatures are expected to drop below 50°F within the next 4 hours.

PREPARATION:

NEW/UNPAINTED SUBSTRATES:

Substrate should be a clean well-held surface free from loose material, dirt, grease, oil and mold. Dust down before proceeding.

On new unpainted plasterboard sheeting, render, brick or timber, spot prime all joints and repaired areas with Sydney Harbour's Limeproof

Undercoat Sealer, then apply two coats of same to entire area.

PREVIOUSLY PAINTED SUBSTRATES:

Provided the surface is clean and sound, Sydney Harbour's Eggshell Acrylic is self-priming and can be applied directly over previously painted surfaces. (Except oil based paints or polyurethanes). High gloss paints or varnishes should be sanded to remove gloss and create a "keyed" surface.

Surfaces painted with oil based paints, or previously painted surfaces with loose, peeling or flaking paint must be made sound by scraping off loose paint. Fill nail holes and cracks with suitable filler, sand and dust off. Spot prime all joints and repaired areas with Sydney Harbour's Limeproof Undercoat Sealer, then apply one coat to entire area. Touch dry two hours. Allow 6 hours dry time.

APPLICATION:

Stir thoroughly prior to use. Apply two coats by brush, spray or a medium nap roller. Touch dry in 1 hour. Allow minimum 2 hours dry time between coats. Allow 6 hours dry time.

COVERAGE RATES:

Approximately 400 to 500 sq. ft. per gallon, depending upon porosity, surface texture and wastage rates.

CLEAN UP:

Water.

COMPLEMENTARY PRODUCTS:

Sydney Harbour's Limeproof Undercoat Sealer (coverage 450 sq. ft. per gallon) is recommended where an undercoat/primer is required when preparing substrate for painting.

PACKAGING:

Sydney Harbour's Eggshell Acrylic is available in Quart, Gallon, and 5 Gallon sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check color before use.

MANUFACTURER/DISTRIBUTOR DETAILS:

Customer Service:

Sydney Harbour Paint Company

Phone: (310)444-2882

Email: admin@shpcompany.com

Web: www.SHPCo.com